


PROJECT	QUANTITY	ITEM NO
---------	----------	---------

F5 Open Fryers



OFG 512 2-well open fryer



Full color touch swipe control



HennyLink® Intelligent Connected Solutions
* Available only in US & Canada



OFG 511 1-well gas
OFG 512 2-well gas
OFG 513 3-well gas
OFG 514 4-well gas

The Henny Penny F5 open fryer is designed from the ground up to make frying high-quality food easier, safer and more efficient for any kitchen. The F5 is built on our reliable 30 lb oil-saving platform but offers a whole new interface that makes everything about this advanced fryer simple. The control consists of a 7-inch touch and swipe screen with a graphics-based operating system that is so intuitive it can reduce initial training by up to 50%.* Built-in Simple Touch Filtration lets crew filter individual vats as needed while continuing to cook in other vats uninterrupted. Just touch the screen three times (or less) to begin filtering. The system drains and filters oil, rinses away crumbs and returns hot filtered oil to the vat in three minutes†. No handles, valves or knobs to pull open or close.

Sensor-activated automatic top-off monitors oil level and automatically replenishes oil from a JIB or reservoir inside the fryer cabinet. This not only eliminates messy manual add backs but significantly extends oil life at peak quality.

Choose from 1, 2, 3, or 4-well, full or split vat configurations.

Henny Penny F5 open fryers recover temperature very quickly and earn the ENERGY STAR® mark with over 50% energy efficiency. Choose from 1, 2, 3, or 4-well, full or split vat configurations.

*Based on a 5-hour training regimen.

**Based on throughput tests according to ASTM standards.

†3 minute filtration possible when following conditions are met:

- Ambient temperatures at or above 72° (22°C)
- Drain pan temperature at or above 160°F (71°C) at the beginning of the filtration cycle
- Filtration media has been previously saturated with oil, but not overly saturated with impurities
- Filtration media is changed at the frequency recommended for your operation

Standard Features

Simple operation

- Custom operating system with intuitive touch and swipe interface
- Learn in minutes, reduce training time by 50%*
- No handles, valves or knobs
- Switch languages easily

Ultra-efficient system

- Full vat, split vat or combination
- 30 lb platform cooks the same size load in 40% less oil than 50 lb vats**
- Automatic top off continuously monitors oil level and adds fresh oil as needed from onboard JIB or reservoir
- Powerful 8 gal (30 L) per minute filter pump
- Improved nozzle design targets corners of vat to clear crumbs
- Faster 3-minute filter time†

- Slanted deck channels oil drips into vat, reducing cleanup
- Bulk oil dispose and supply (additional charge)

Kitchenproof design

- Heavy-duty stainless steel vats with 7-year warranty
- Durable 4 mm, 7-inch recessed touchscreen control panel
 - 99 available cooking programs
 - Eco and preheat modes
 - Load compensation
 - Proportional control
 - Filter tracking
- High-limit temperature protection with reset switch and control-panel troubleshooting guide
- HennyLink®
 - Wireless connectivity
 - Asset status and fryer utilization

- Heavy-duty basket rest removes easily for cleaning
- High-efficiency burners with solid state ignition
- 4 heavy-duty casters, 2 locking

Accessories shipped with unit

- Fry baskets (additional charge)
 - 1 full basket per well OR
 - 2 half baskets per well
- 1 basket support for each vat
- Installation and operating manual

Optional accessories

- ODS 310 or ODS 460 50 lb oil disposal shuttle
- Fry well covers
- Prime Filter Packets, HD pads or powder
- SmartFilter™ paper
- Prime Cleaner
- Oil dispensing jug
- Gas line

☐ APPROVED	☐ APPROVED AS NOTED	☐ RESUBMIT
AUTHORIZED SIGNATURE		DATE



F5 Open Fryers

OFG 511 1-well gas
OFG 512 2-well gas
OFG 513 3-well gas
OFG 514 4-well gas



	OFG 511	OFG 512	OFG 513	OFG 514
Dimensions				
Width	16.63 in (422 mm)	31.10 in (790 mm)	46.70 in (1186 mm)	62.20 in (1580 mm)
Depth	36.90 in (938 mm)	32.94 in (837 mm)	32.94 in (837 mm)	32.94 in (837 mm)
Height	46.58 in (1184 mm)	46.58 in (1184 mm)	46.58 in (1184 mm)	46.58 in (1184 mm)

Crated

Width	21 in (533 mm)	36 in (914 mm)	51 in (1295 mm)	67 in (17202 mm)
Depth	41 in (1041 mm)	36 in (914 mm)	36 in (914 mm)	36 in (914 mm)
Height	55 in (1397 mm)	55 in (1397 mm)	55 in (1397 mm)	55 in (1397 mm)
Volume	27 ft³ (0.76 m³)	42 ft³ (1.2 m³)	57 ft³ (1.6 m³)	77 ft³ (2.2 m³)
Weight	340 lb. (154 kg)	509 lb. (231 kg)	738 lb. (335 kg)	989 lb. (449 kg)

Heating natural gas or liquid petroleum

4 burners	8 burners	12 burners	16 burners
75,000 BTU/hr	150,000 BTU/hr	225,000 BTU/hr	300,000 BTU/hr
19.8 kW	39.6 kW	59.4 kW	79.2 kW
0.75 in gas connection	0.75 in gas connection	1.0 in gas connection	1.0 in gas connection

Oil capacity

Full vat: 30 lb, 16 qt (14 kg, 15 L)
 Split vat: 15 lb, 7.9 qt (6.8 kg, 7.5 L)

Electrical

Volts	Phase	Hertz	kW	Amps	Wire*	Cord & Plug
120	1	60	N/A	12.2	2+G	NEMA 5-15P
230	1	50		7.0	1NG	Contact Henny Penny

* Units shipped without power cord and plug must have power cord and plug installed on site by a qualified electrician.

Required clearances

Sides: 2 in (51 mm) from combustible materials or other heat producing equipment; otherwise no clearance required.
 Back: 6 in (152 mm) air flow, connections.
 Front: 30 in (762 mm) remove drain pan
 Top: Flue duct must be free to discharge combustible gas

Bidding specifications

Provide Henny Penny F5 Series model OFG 511, 512, 513, or 514 reduced oil capacity gas open fryer with touch-and-swipe control and 30 lb (14 kg) oil capacity per well. Unit may be ordered with full or split vat(s).

Unit shall incorporate:

- 7" full color touchscreen control with up to 99 available cooking programs, eco and preheat modes, load compensation, proportional control, filtration tracking, clean-out mode, multiple language settings, USB port for each well and WiFi connectivity (available soon)
- Automatic oil top off system from jug-in-box or other reservoir in fryer cabinet
- Integral touch-activated filter system that filters oil from one vat while cooking continues in other vats
- Oil drain pan with 4 glides with sensor warning when pan is not properly in place
- Unit qualifies for the ENERGY STAR® mark.
- Fry vats of heavy duty stainless steel with 7-year warranty
- 4 heavy-duty casters, 2 locking

Laboratory certifications



Continuing product improvement may subject specifications to change without notice.

24 Hour Technical Support:
 Henny Penny Technical Service
 800 417.8405
technicalservices@hennypenny.com

© 2026 Henny Penny Corporation, Eaton, OH 45320 USA Revised 11162023

Henny Penny Corporation
 PO Box 60 Eaton OH 45320 USA
 800 417.8417
 +1 937 456.8400
 +1 937 456.8434 Fax
www.hennypenny.com

HENNY PENNY